



PB IW 60

PUNCHING		INCH
Diameter x max. thickness		Ø 1,10 x 0,59
Diameter x thickness		Ø 1,49 x 0,43
Diameter x min. Thickness Optional) (*)		Ø 4,33 x 0,11
Stroke		2,16
Stroke count in (20mm)		X1, 02
Throat depth		8,66
Working height		37
SHEET METAL SHEAR		
Sheet metal		7,87 x 0,78
Sheet metal		11,81 x 0,59
Blade lenght		12,48
Shearing with angle		3,14 x 0,39
Working height		37
ANGLE SHEAR		
Angle section (90°)		4,72 x 4,72 x 0,472
Angle section (45°)		3,14 x 0,314
Working height		44,88
STEEL BAR SHEARING		
Round / Square		Ø1,57 - Ø1,37
NOTCHING		
Thickness		0,39
Width		1,65
Depth		3,93
V Depth		2,36
Angle flange		3,93 x 0,393
Working height		37
OPTIONAL TOOLS		
U-I Section blades		3,14 x 1,77
T Section blades		3,14 x 0,393
Special V-notching tooling		3,93 x 3,93 x 0,393
V bending Press brake	Bar bend. max. Capacity	5,90 x 0,47
	Sheet bend. max.capacity	
Punching on notcher	Bar bend. max. Capacity	4,33
	Sheet bend. max.capacity	0,787 x 0,47
TECHNICAL DATA		
Motor power		5,36 HP
Weight		2775 lbs
Machine dimensions		59,4 x 23,22 x 61,81
Power (Pressure)		60 tons